



MOTOR OIL SL 15W-40

Product Description:

MOTOR OIL SL 15W-40 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

MOTOR OIL SL 15W-40 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

MOTOR OIL SL 15W-40 meets the following performance criteria:

ACEA A3/B3

MB 229.1

VW 505.00

API SL



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m ³	ASTM D4052	878
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	94
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.3
Viscosity Index		ASTM D2270	141
Viscosity CCS @-20°C, max	cP	ASTM D5293	5160
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D874	1.05

Product Nr: 42080

Date Superseded: 15-01-2019

Date Issued: 10-121-2019

Revision nr: 04