



MOTOR OIL SL/CF 10W-40

Product Description:

MOTOR OIL SL/CF 10W-40 is a universal high performance semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SL/CF 10W-40 is formulated with high quality re-refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SL/CF 10W-40 meets the following performance criteria:

API SL/CF

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	862
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	101
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	15.5
Viscosity Index		ASTM D2270	162
Viscosity CCS @-25°C, max	cP	ASTM D5293	4610
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	7.4
Sulphated Ash	%Wt	ASTM D874	0.91

Product Nr: 42090

Date Superseded: 15-01-2018

Date Issued: 10-12-2019

Revision nr: 05

