



ENGINE OIL HDX 15W-40

Product Description:

ENGINE OIL HDX 15W-40 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

ENGINE OIL HDX 15W-40 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

ENGINE OIL HDX 15W-40 meets the following performance criteria:

Approved	MB Approval 228.3	Volvo VDS-3	Renault RLD-2	MACK EO-N
Meets	API CI-4/ SL Global DHD-1 CAT ECF-1a	ACEA E7 JASO DH-1 MAN M 3275	MB 228.1 Deutz DQC-III Cummins CES 2077/20078	DDC 93K215 MTU Type 2



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m ³	ASTM D4052	883
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	100
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	140
Viscosity CCS @-20°C, max	cP	ASTM D2270	5740
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	11.6
Sulphated Ash	%Wt	ASTM D874	1.5

Product Nr: 42560

Date Superseded: 01-05-2018

Date Issued: 12-12-2019

Revision nr: 09