



# MOTOR CYCLE OIL 4T 15W-50

## Product Description:

**MOTOR CYCLE OIL 4T 15W-50** is a high performance semi synthetic engine oil especially developed for use in air-, oil-, and water-cooled 4-stroke motorcycles to provide excellent protection towards engine, gearbox and wet clutches and ensures the highest possible reliability even under the most severe operation conditions.

**MOTOR CYCLE OIL 4T 15W-50** is based on a mixture of high performance hydrocracked- and mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Controlled frictional properties eliminate clutch slippage, effectively improving the driveability of the vehicle.

**MOTOR CYCLE OIL 4T 15W-50** meets the following performance criteria:

**API SL      JASO MA2**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-50
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	874
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	127
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	17.8
Viscosity Index		ASTM D2270	156
Viscosity CCS @-20°C, max	cP	ASTM D5293	5020
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D874	1.25

**Product Nr:** 42970

**Date Superseded:** 08-02-2018

**Date Issued:** 13-12-2019

**Revision nr:** 03