



AUTOGEAR OIL EP 85W-140

Product Description:

AUTOGEAR OIL EP 85W-140 is an universal high performance mineral EP gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-4 is been required.

AUTOGEAR OIL EP 85W-140 is formulated with high refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good Extreme Pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR OIL EP 85W-140 meets the following performance criteria:

API GL-4 MIL-L-2105



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W-140
Density@15°C	kg/m ³	ASTM D4052	904
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	437
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	29.8
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	< 150000
Viscosity Index		ASTM D2270	97
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-15

Product Nr: 43040

Date Superseded: 08-02-2018

Date Issued: 13-12-2019

Revision nr: 03