



ATF CVT FLUID

Product Description:

ATF CVT FLUID is a fully synthetic ultra-high performance CVT fluid formulated with selected base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts.

ATF CVT FLUID is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Good thermo-and oxidation stability.
- Extended drain interval possible.
- Excellent anti-wear, anti-rust and anti-corrosion technology.
- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials

ATF CVT FLUID meets the following performance criteria:

MB 236.20	Ford M2C928-A	BMW 83 22 0 136 376	BMW 83 22 0 429 154
VW G 052 180	Toyota CVTF-TC	Toyota CVT-FE	Nissan NS-1 / NS-2 / NS-3
Honda HMMF	Honda HCF-2	Mitsubishi SP-III	Mitsubishi CVTF-J1
Mitsubishi CVTF-J4 / CVTF-J4+		Suzuki CVTF TC / 3320	Suzuki NS-2
Subaru ECVT	Subaru iCVT	Daihatsu Ammix CVT	Suzuki CVTF Green 1 / 1V
Hyundai SP-III	EZL 799 / 799A	Chrysler/Jeep NS-2	JWS 3320
VW G 052 516			



Property	Unit	Test Method	Typical Value
Color		Visual	Amber
Density @15°C	kg/m ³	ASTM D4052	846
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	34.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.3
Viscosity Index		ASTM D2270	186
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-45

Product Nr: 43250
Date Superseded: 10-04-2018

Date Issued: 16-12-2019
Revision nr: 04