



SUPER TRACTOR OIL

10W-40

Product Description:

SUPER TRACTOR OIL 10W-40 is a high quality universal synthetic so called “Super Tractor Oil Universal” (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed “wet brakes”. This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).



SUPER TRACTOR OIL 10W-40 is formulated on synthetic base stocks in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

SUPER TRACTOR OIL 10W-40 exceeds the following performance criteria:

Engine Spec	API CG-4/CF-4/CE/SF	MB 228.1	ACEA E3
UTTO Spec	JD J20C/D, J27	Ford M2C86B/C	Ford M2C134D
	MF M1135/1139	MF M1143/1145	Cat TO-2
	Allison C-4	ZF TE-ML 06A, 06B, 06C, 06D, 06E, 06H 07B	
	NH 82009201, 2, 3		
Hydr Spec	Eaton M-2950S	Eaton 1-280-S	Danfoss

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	860
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	90.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	163
Viscosity CCS @-25°C,	cP	ASTM D5293	4600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.9

Product Nr: 43260
Date Superseded: 30-10-2017

Date Issued: 16-12-2019
Revision nr: 02