



# AUTOGEAR OIL TX 75W-80

## Product Description:

**AUTOGEAR OIL TX 75W-80** is a high quality fuel saving synthetic thermally stable long life gear lubricant designed for passenger- and commercial vehicles using manual transmissions fitted with different synchronizers including latest ones based on carbon.

**AUTOGEAR OIL TX 75W-80** is based on high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo and oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including latest carbon.
- Good frictional properties provide improved fuel economy and smoother shift ability.

**AUTOGEAR OIL TX 75W-80** meets the following performance criteria.:

**Approved**      **MAN 341 Z4**

**Exceeds**      **API GL-4**              **Volvo 97307**              **Renault B0032/2**  
**IVECO**                      **Eaton Europe**              **DAF**  
**ZF TE-ML 01L,02L,08,13,16K**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	75W-80
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	861
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	60.6
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	10.1
Brookfield Viscosity @-40°C	cP	ASTM D2983	99800
Viscosity Index		ASTM D2270	155
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39

**Product Nr:** 43330  
**Date Superseded:** 30-03-201

**Date Issued:** 13-12-2019  
**Revision nr:** 06